




MERCURY TWO-STROKES

250-75

Models ⁽¹⁾	 250 • 225 SW EFI EFI/ SW EFI	 200 • 150 SALTWATER/ SALTWATER EFI	125 • 115	90 • 75	60 • 50 • 40 + BIGFOOT 3 CYL.
Kilowatts⁽²⁾	184 • 165 kW	147 • 110 kW	91.9 • 84.5 kW	66.2 • 55.1 kW	44.1 • 36.8 • 29.4 kW
Max. RPM at Full Throttle	5000-5800	200 SW: 5000-5600 200 SW EFI: 5000-5800 150 SW • 150 SW EFI: 5000-6000	4750-5250	90: 5000-5500 75: 4750-5250	5000-5500
Cylinders	V-6 (60° vee)	V-6 (60° vee)	4 (in-line)	3 (in-line)	3 (in-line)
Displacement	3032 cc	2507 cc	1848 cc	1386 cc	967 cc
Bore / Stroke	92 mm × 76 mm	89 mm × 67 mm	89 mm × 75 mm	89 mm × 75 mm	76 mm × 71 mm
Cooling System	Water cooled w/ thermostat and pressure controlled	Water cooled w/ thermostat and pressure controlled	Water cooled w/ thermostat and pressure controlled	Water cooled w/ thermostat and pressure controlled	Water cooled w/ thermostat
Ignition	PCM 038	Modular CDI SW EFI: PCM 038	Modular CDI	Modular CDI	Modular CDI
Starting	Electric (turnkey)	Electric SW EFI: Electric (turnkey)	Electric	Electric	Electric
Gear Ratio	1.75:1	1.87:1	2.07:1	2.33:1	60: 1.64:1 60 BIGFOOT: 2.33:1 50 • 40: 1.83:1
Gear Shift	F-N-R	F-N-R	F-N-R	F-N-R	F-N-R
Steering	Remote	Remote	Remote	Remote	Remote
Alternator System⁽³⁾	Belt driven 60 amp (756 watt)	40 amp (504 watt) SW EFI: Belt driven 60 amp (756 watt)	18 amp (227 watt)	18 amp (227 watt)	16 amp (201 watt)
Trim Positions	Power trim standard	Power trim standard	Power trim standard	Power trim standard	60 • 50: Gas assist (Power trim optional) 60 BIGFOOT • 40: Power trim standard
Fuel Tank	Optional	Optional	Optional	Optional	Standard
Fuel Requirements	Leaded or unleaded 90 RON min.	Leaded or unleaded 90 RON min.	Leaded or unleaded 90 RON min.	Leaded or unleaded 90 RON min.	Leaded or unleaded 90 RON min.
Weight⁽⁴⁾	250 SW EFI • 225 SW EFI: 220 kg 225 EFI: 218 kg	200 SW: 182 kg 150 SW: 183 kg 200 SW EFI • 150 SW EFI: 187 kg	158 kg	139 kg	60: 100 kg 60 BIGFOOT: 109 kg 50 • 40: 93 kg
Recommended Boat Transom Height	XL 635 mm 225 EFI: Long 508 mm	Long 508 mm XL 635 mm	Long 508 mm	Long 508 mm Shaft extension kit available XL 635 mm	Short 381 mm Long 508 mm 60 BIGFOOT • 40: Long 508 mm
Induction System	Loop-charged (EFI)	Loop-charged (3 carb) SW EFI: Loop-charged (EFI)	Loop-charged (4 carb)	Loop-charged (3 carb)	Loop-charged (3 carb)
Exhaust	Through prop	Through prop	Through prop	Through prop	Through prop
Oil Injection	Standard	Standard	Standard	Standard	Standard
Counter Rotation	Available on SALTWATER models only	Available on XL models only	N/A	N/A	N/A

(1) Model offering may vary from one country to another. Please see your local dealer for specific information.

(2) Measured at propshaft in accordance with ICOMIA 28.

 SmartCraft integrated Marine technology standard.

(3) Requires rectifier to complete installation manual versions, Standard on 4 Sailpower model.

(4) Dry weight specification is for lightest model and excludes engine oil, rigging hardware and propeller.

